



XSTREAM RAD SEAL

APPLICATION

- Recommended for the rapid, permanent repair of small leaks in radiators, engine blocks and cylinder heads.

PROPERTIES

- An aqueous dispersion of finely ground inert filler, with thickener, anti-corrosion agents and water soluble lubricants.
- Leave in the system all year round to prevent leaks as they occur.
- Harmless to rubber hoses and gaskets.
- Synthetic technology repairs cooling system leaks quickly and permanently.
- Compatible with antifreeze and coolant.
- Suitable for use in all types of vehicle coolant systems including turbo charged vehicles.

TYPICAL INSPECTION DATA:

Appearance:	Thick dark green liquid
Specific Gravity @ 20°C	1.000
PH value	7.6
Sufficient to treat	20 litres

DIRECTIONS FOR USE

- Drain and refill radiator then run engine till warm.
- Shake container thoroughly and pour contents directly into the radiator. Do not add to the radiator expansion tank.
- Run engine for a few minutes to allow Rad Seal to harden.
- Larger leaks may require the hole to be plugged with wire wool before use.
- In older vehicles it is advisable to use Comma Rad Clean before the use of Rad Seal.

HANDLING

- Avoid extremes of temperature.
- Store under cover.

SHELF LIFE

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.