



## Eco-Z 0W-20

Fully Synthetic

**Recommended by Comma for applications requiring:**

MB 229.71; BMW LL17FE+ (backwardly compatible with BMW LL14FE+); Opel / Vauxhall OV0401547; ILSAC GF-5; ACEA C5, API SN, SN PLUS, SN-RC

### Product Features:

- Fully synthetic, high performance 0W-20 oil for modern petrol & diesel engines.
- Provides excellent low speed pre-ignition (LSPI) protection and protects after-treatment systems including petrol particulate filters.
- Helps to deliver high fuel economy as per latest OEM requirements.

For the latest Opel/Vauxhall, Mercedes Benz and BMW cars requiring high level of fuel economy and LSPI protection.

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

### Typical Inspection Data:

Density @ 20°C	0.841 g/cm <sup>3</sup>
Viscosity @ 100°C	8.2 cSt
Viscosity @ 40°C	41 cSt
Viscosity Index	180
Viscosity CCS @ -35°C	5500 cP
T.B.N.	7.9 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.09%
Calcium	0.11%
Phosphorus	0.08%
Colour	Brown
Flash Point (Closed Cup)	210°C
Pour Point	-48°C

UPDATED: 30-01-2019